

# Cocoa Programming Guidelines

Wojciech Nagrodzki

April 12, 2015



Special thanks to: Krzysztof Profic, Bartłomiej Hyży, Grzegorz Wikiera,  
Piotr Węgrzynek and Daniel Garbień

# Contents

<b>Code Appearance</b>	3
Class names are not prefixed usually	3
Protocol names indicates behaviour	3
Header files follow a structure	3
Implementation files are divided by pragma marks	5
Property attributes are kept in an order	5
Protocols and constants are prefixed with a class name	6
IBOutlets are declared privately	6
Classes may have additional header file for subclasses	6
Methods return early and often	7
Methods are not bisected with conditionals	8
Methods can be prefixed with get	8
 <b>General rules</b>	 9
Header files are imported only if necessary	9
Delegate methods always pass the sender	9
Property's default values are documented conditionally	9
Init methods take only mandatory parameters	10
Accessors are not used in init and dealloc	10
Abstract classes can be faked with assertion	10
Abstract methods raise exceptions	11
The highest level of abstraction is used by default	11
Exceptions are not used to control flow	11
Lazy loading reduces memory footprint	12
No object register other objects as observers	12
Methods do not return NSError object	12
Custom errors belong to error domains	13
Properties can be added to existing classes	13
Object's equality requites three methods to be provided	14
 <b>Concurrency</b>	 15
Prefer dispatch queues to locks for mutual exclusion	15
Multiple readers one writer	16
NSOperation can be cancelled before it begins execution	16
 <b>UIView</b>	 17
View is usually initialised in two ways	17
The interface of generic view	18
The interface of specific view	18
 <b>UIViewController</b>	 19
Properties affecting user interface	19

View controller containment	19
Container specific items are provided by a property	19
Container is accessible from contained view controllers	20
The deallocation problem	20
<b>Core Data</b>	21
Category provides helper methods to managed object	21
Custom objects are stored as transformable attributes	21
Objective-C types are stored through NSValue	22

# Code Appearance

Hardly any software is maintained by its original author for its whole life. Writing code in an unified way helps engineers to understand it more quickly.

## Class names are not prefixed usually

Prefixes are used only for classes which are to be shared between applications.

## Protocol names indicates behaviour

Most protocols group related methods that aren't associated with any class in particular. This type of protocol should be named so that the protocol won't be confused with a class. A common convention is to use a gerund ("...ing") form:

- `NSLocking`            Good
- `NSLock`                Poor (seems like a name for a class)

Some protocols group a number of unrelated methods (rather than create several separate small protocols). These protocols tend to be associated with a class that is the principal expression of the protocol. In these cases, the convention is to give the protocol the same name as the class. An example of this sort of protocol is the `NSObject` protocol.

## Header files follow a structure

Each header file should be succinct, and comply with the following declaration's order:

1. Imports
2. Forward class declarations
3. Enumeration types
4. Constants
5. Notification names and its user info dictionary keys
6. Delegate protocol
7. Data source protocol
8. Class interface

A class interface has a fixed structure as well:

1. Properties
2. Data source property
3. Delegate property
4. Class methods
5. Instance methods

Please pay attention to the linespacing, it is also a rule.

```
#import <Foundation/Foundation.h>

@class ExampleClass;

typedef NS_ENUM(NSInteger, Enumeration) {
    EnumerationA,
    EnumerationB
};

extern CGFloat const ExampleClassDefaultHeight;

extern NSString * const ExampleClassWillPerformActionNotification;
extern NSString * const ExampleClassDidPerformActionNotification;
extern NSString * const ExampleClassActionNameKey;

@protocol ExampleClassDelegate <NSObject>

- (void)exampleClass:(ExampleClass *)exampleClass didPerformAction:(Action *)action;

@optional

- (void)exampleClass:(ExampleClass *)exampleClass willPerformAction:(Action *)action;

@end

@protocol ExampleClassDataSource <NSObject>

- (NSInteger)exampleClassNumberOfActions:(ExampleClass *)exampleClass;

@end

@interface ExampleClass : NSObject

@property (strong, nonatomic) NSURL * initialProperty;
@property (weak, nonatomic) id<ExampleClassDataSource> dataSource;
@property (weak, nonatomic) id<ExampleClassDelegate> delegate;

+ (id)exampleClassWithInitialProperty:(NSURL *)initialProperty;
- (id)initWithInitialProperty:(NSURL *)initialProperty;
- (void)performAction;

@end
```

## Implementation files are divided by pragma marks

Methods in an implementation file appear in the same order as they are declared in the header. They are also grouped by pragma marks similar to the following:

```
#pragma mark - Public Properties
#pragma mark - Public Class Methods
#pragma mark - Public Instance Methods
#pragma mark - IBActions
#pragma mark - Overridden
#pragma mark - Private Properties
#pragma mark - Private Class Methods
#pragma mark - Private Instance Methods
#pragma mark - Protocols
#pragma mark - Notifications
```

In need of greater granularity:

```
#pragma mark - Overridden (UIView)
#pragma mark - Overridden (UIContainerViewControllerCallbacks)
#pragma mark - Overridden (UIViewControllerRotation)
```

## Property attributes are kept in an order

The attributes are kept in the same order through all property declarations.

```
[assign | weak | strong | copy] + [nonatomic | atomic] + [readonly | readwrite] + [getter = ]
```

None of the attributes can be omitted with the exception of readwrite.

```
@property (assign, nonatomic) CGFloat height;
@property (strong, nonatomic) UIColor * color;
@property (copy, nonatomic) NSString * name;
@property (weak, nonatomic) id <UITableViewDelegate> delegate;
```

Getters for boolean properties, if they are adjectives, are renamed in the following manner:

```
@property (assign, nonatomic, getter = isVisible) BOOL visible;
@property (assign, nonatomic, getter = isEnabled) BOOL enabled;
@property (assign, nonatomic, getter = isTracking) BOOL tracking
```

**Important:** The copy attribute is often used with NSString, NSArray or NSDictionary to preserve encapsulation, since the value passed into the setter might be an instance of mutable subclass.

## Protocols and constants are prefixed with a class name

Protocols, notification names, enumeration types and other constants that refer to a particular class are prefixed with the name of that class.

```
typedef NSInteger, UITableViewStyle) {
    UITableViewStylePlain,
    UITableViewStyleGrouped
};

UIKIT_EXTERN NSString *const UITableViewIndexSearch;

UIKIT_EXTERN const CGFloat UITableViewAutomaticDimension;

UIKIT_EXTERN NSString *const UITableViewSelectionDidChangeNotification;

@protocol UITableViewDelegate<NSObject, UIScrollViewDelegate>
...
```

## IBOutlets are declared privately

Outlets are defined as weak properties at the top of a class extension, and divided by one line from the other properties.

```
@interface PanelViewController ()

@property (weak, nonatomic) IBOutlet UIButton * infoButton;
@property (weak, nonatomic) IBOutlet UIButton * closeButton;
@property (weak, nonatomic) IBOutlet UILabel * descriptionLabel;

@property (weak, nonatomic) UIView * overlayView;

@end
```

## Classes may have additional header file for subclasses

Private methods and properties are never exposed. To provide a subclass access to them, they have to be declared in a category entitled ForSubclassEyesOnly. It should be placed in a separate header file, named in the following manner: [Class Name] + Subclass.h.

**Tip:** UIGestureRecognizerSubclass.h is a good example of that approach.

## Methods return early and often

A nesting usually makes code harder to read.

```
- (BOOL)loginUser:(NSString *)user withPassword:(NSString *)password
{
    if (user.length >= 6) {
        if ((password.length >= 8) {
            // the actual logging code
        }
    }
    return NO;
}
```

Getting invalid cases out of the way first will keep the working code with one level of indentation, and ensure that all parameters are valid. This paradigm is called The Golden Path.

```
- (BOOL)loginUser:(NSString *)user withPassword:(NSString *)password
{
    if (user.length < 6) return NO;
    if (password.length < 8) return NO;

    // actual logging code
}
```

This approach has one more advantage, it is easier to add an error handling later on.

```
- (BOOL)loginUser:(NSString *)user withPassword:(NSString *)password error:(NSError **)error
{
    if (user.length < 6) {
        if (error != NULL)
            *error = [NSError errorWithDomain:ExampleDomain
                                     code:1001
                                     userInfo:@{NSLocalizedDescriptionKey: @"User has to..."}];

        return NO;
    }

    if (password.length < 8) {
        if (error != NULL)
            *error = [NSError errorWithDomain:ExampleDomain
                                     code:1002
                                     userInfo:@{NSLocalizedDescriptionKey: @"Password has to..."}];

        return NO;
    }

    // actual logging code
}
```



## Methods are not bisected with conditionals

The following method structure is not acceptable.

```
- (void)method
{
    if (self.valueX == 10) {
        // perform some actions
    }
    else {
        // perform some other actions
    }
}
```

Bisection can be removed by returning within an if statement.

```
- (void)method
{
    if (self.valueX == 10) {
        // perform some actions
        return;
    }

    // perform some other actions
}
```

In one case bisection is allowed.

```
- (void)method
{
    if (self.valueX == 10) {
        // perform some actions
    }
    else {
        // perform some other actions
    }

    // perform some actions no matter what
}
```

## Methods can be prefixed with get

Get prefix is used only in situations when a value is returned indirectly via a memory address.

```
@interface NSValue : NSObject <NSCopying, NSSecureCoding>

- (void)getValue:(void *)value;

@end
```

# General rules

## Header files are imported only if necessary

Importing a header file is allowed:

- if class needs to conform to a protocol (header with protocol declaration)
- if class is inheriting from another class (header with superclass declaration)
- if class uses enums in its interface (header with enums declarations)

In any other case a forward declaration should be applied.

## Delegate methods always pass the sender

A delegation method passes the sender as the first parameter. It is a good practice to use will/did paradigm.

```
- (NSInteger)exampleClassNumberOfActions:(ExampleClass *)exampleClass
- (void)exampleClass:(ExampleClass *)exampleClass willPerformAction:(Action *)action;
- (void)exampleClass:(ExampleClass *)exampleClass didPerformAction:(Action *)action;
```

## Property's default values are documented conditionally

The `alloc` method clears out the memory allocated for an object's properties, by setting it to zero. If a property value is not altered during the initialisation, a note about its default value may be omitted.

```
/*
 * A Boolean value that determines whether the view is hidden.
 */
@property(nonatomic, getter=isHidden) BOOL hidden // represented by zeroed memory
```

On the contrary, if the default value is changed, a mention about it is included.

```
/*
 * Defines the anchor point of the layer's bounds rectangle.
 * The default value of this property is (0.5, 0.5).
 */
@property (nonatomic) CGPoint anchorPoint // not represented by zeroed memory
```

## Init methods take only mandatory parameters

All settings required to a proper initialisation are passed as initialiser's parameters. They are later accessible through readonly properties.

```
@property (strong, nonatomic, readonly) DownloaderMode downloaderMode;

- (id)initWithDownloaderMode:(DownloaderMode)downloaderMode;
```

**Tip:** If you need a convenience method to create instances, consider creating factory methods.

## Accessors are not used in init and dealloc

Instance subclasses may be in an inconsistent state during `init` and `dealloc` method execution, hence code in those methods must avoid invoking accessors.

```
- (id)init
{
    self = [super init];
    if (self) {
        _foo = [NSMutableSet set];
    }
    return self;
}

- (void)dealloc
{
    [_titleLabel removeObserver:self forKeyPath:@"text"];
}
```

## Abstract classes can be faked with assertion

Creating instances of an abstract class is foiled by the following assertion.

```
- (id)init
{
    self = [super init];
    if (self) {
        NSAssert1([self isKindOfClass:[MyAbstractClass class]] == NO,
                  @"%@ is an abstract class. Please do not create instances of it.", [self class]);
    }
    return self;
}
```

## Abstract methods raise exceptions

Forcing a subclass to provide an implementation of a method is accomplished by raising an exception in superclass method.

```
- (void)abstractMethod
{
    [NSException raise:NSInternalInconsistencyException
                 format:@"It's template method. Implementation must be provided in subclass."];
}
```

## The highest level of abstraction is used by default

Lower levels are used only when more control is required. For example, instead using GCD:

```
dispatch_sync(dispatch_get_main_queue(), ^{
    // code
})
```

Use an operation queue.

```
[[NSOperationQueue mainQueue] addOperationWithBlock:^(
    // code
)];
```

## Exceptions are not used to control flow

The general pattern is that exceptions are reserved for programming or unexpected runtime errors, such as out-of-bounds collection access, attempts to mutate immutable objects, sending an invalid message, or losing the connection to the window server. A program catching such exception should quit soon afterwards. Exceptions must not be used to control flow in favor of `NSError` objects. When developing a class or a framework exceptions are thrown to indicate that class or framework are being misused:

```
- (void)abstractMethod
{
    [NSException raise:NSInternalInconsistencyException
                 format:@"It's template method, you need to implement it in your subclass"];
}
```

## Lazy loading reduces memory footprint

Creating an object on demand reduces initialisation time of a containing class. The following getter implementation is not thread safe, as two threads might try to initialise `_cacheDictionary` at the same time.

```
- (NSMutableDictionary *)cacheDictionary
{
    if (_cacheDictionary == nil) {
        _cacheDictionary = [NSMutableDictionary dictionary];
    }
    return _cacheDictionary;
}
```

## No object register other objects as observers

Object registers only itself as an observer.

```
[obj addObserver:self forKeyPath:@"isExecuting" options:NSKeyValueObservingOptionNew context:NULL];
```

Unregistering follows the same rule.

```
[obj removeObserver:self forKeyPath:@"isExecuting" context:NULL];
```

## Methods do not return NSError object

A failure is indicated by `nil` or `NO` returned by a method. Success similarly by `YES` or not-`nil` pointer.

```
- (id)initWithContentsOfURL:(NSURL *)aURL;
- (BOOL)writeToURL:(NSURL *)aURL atomically:(BOOL)atomically;
```

`NSError` object is used only for providing additional information about a failure.

```
- (id)initWithContentsOfURL:(NSURL *)aURL options:(NSDataReadingOptions)mask error:(NSError **)errorPtr;
- (BOOL)writeToURL:(NSURL *)aURL options:(NSDataWritingOptions)mask error:(NSError **)errorPtr
```

Therefore you should always check if the return value is `nil` or `NO` before attempting to do anything with an `NSError` object. Moreover, you ought to check the domain before examining the error code.

## Custom errors belong to error domains

A custom error have both the error domain and error code defined.

```
extern NSString * const MyErrorDomain;

enum : NSUInteger
{
    MyErrorCode1,
    MyErrorCode2,
    MyUnknownErrorCode,
};
```

Both parameters including localised description are used during an error initialisation.

```
if (error != NULL) {
    if(error_situation_1) {
        *error = [NSError errorWithDomain:MyErrorDomain
                                code:MyErrorCode1
                                userInfo:@{NSLocalizedDescriptionKey: @"Description of error 1"}];
    }
    else if (error_situation_2) {
        *error = [NSError errorWithDomain:MyErrorDomain
                                code:MyErrorCode2
                                userInfo:@{NSLocalizedDescriptionKey: @"Description of error 2"}];
    }
    else {
        *error = [NSError errorWithDomain:MyErrorDomain
                                code:MyUnknownErrorCode
                                userInfo:@{NSLocalizedDescriptionKey: @"Unknown error"}];
    }
}
```

## Properties can be added to existing classes

A property is added to an existing class by using associated objects. Please pay attention to the way the key is defined.

```
static void * const navigationItemKey = (void *)&navigationItemKey;

- (void)setNavigationItem:(UINavigationController *)navigationItem
{
    objc_setAssociatedObject(self,
                            navigationItemKey,
                            navigationItem,
                            OBJC_ASSOCIATION_RETAIN_NONATOMIC);
}
```

```

- (UINavigationController *)navigationItem
{
    return objc_getAssociatedObject(self, navigationItemKey);
}

```

## Object's equality requires three methods to be provided

`isEqualToYourClassName`: provides the actual logic and works only with the instances of receiver's class. Passing an object of any other class triggers the assertion. `isEqual`: works with any object. `hash`: usually XORs the hash values of the properties.

```

- (BOOL)isEqualToPerson:(Person *)person
{
    if (person == nil) return NO;

    NSParameterAssert([object isKindOfClass:[Person class]]);

    return ((self.name == nil && person.name == nil) || [self.name isEqual:person.name]) &&
        ((self.weight == nil && person.weight == nil) || [self.weight isEqual:person.weight]) &&
        ((self.age == nil && person.age == nil) || [self.age isEqual:person.age]);
}

- (BOOL)isEqual:(id)object
{
    if ([self isKindOfClass:[object class]]) return [self isEqualToPerson:object];
    return NO;
}

- (NSUInteger)hash
{
    return self.name.hash ^ self.surname.hash ^ self.age.hash;
}

```

If mutable subclass has to be provided, all the occurrences of `isKindOfClass`: should be replaced with `isKindOfClass`:

# Concurrency

Recommended reading [Concurrent Programming – objc.io](http://objc.io)

**Important:** To avoid priority inversion problems with Grand Central Dispatch use default queue priority `DISPATCH_QUEUE_PRIORITY_DEFAULT` in almost all cases.

## Prefer dispatch queues to locks for mutual exclusion

Critical sections of the code are isolated by a serial dispatch queue. It allows the calling thread to continue execution in contrast to `NSLock` and `@synchronized` directive.

```
- (id)init
{
    self = [super init];
    if (self) {
        NSString * label = [NSString stringWithFormat:@"%s.isolationQueue.%p", [self class], self];
        _isolationQueue = dispatch_queue_create([label UTF8String], DISPATCH_QUEUE_SERIAL);
    }
    return self;
}
```

The above mentioned queue label helps finding the owning object of the queue while debugging.

```
- (void)startDownloading
{
    dispatch_async(self.isolationQueue, ^{
        // critical code section A
    })
}

- (void)cancelDownloading
{
    dispatch_async(self.isolationQueue, ^{
        // critical code section B
    })
}
```

**Important:** The queue is not created lazily as it would require the getter to be thread safe.



## Multiple readers one writer

A concurrent dispatch queue is used to synchronise access to a property in an efficient way.

```
- (id)init
{
    self = [super init];
    if (self) {
        NSString * queueLabel = [NSString stringWithFormat:@"%s.syncQueue.%p", [self class], self];
        _syncQueue = dispatch_queue_create([queueLabel UTF8String], DISPATCH_QUEUE_CONCURRENT);
    }
    return self;
}
```

Dispatch barrier async runs the block after all previously scheduled blocks are completed and before any following blocks are run.

```
- (void)setObject:(id)anObject forKey:(id <NSCopying>)aKey
{
    aKey = [aKey copyWithZone:NULL];
    dispatch_barrier_async(self.syncQueue, ^{
        [self.mutableDictionary setObject:anObject forKey:aKey];
    });
}

- (id)objectForKey:(id)aKey
{
    __block id object;
    dispatch_sync(self.syncQueue, ^{
        object = [self.mutableDictionary objectForKey:aKey];
    });
    return object;
}
```

## NSOperation can be cancelled before it begins execution

The main method checks if an operation is cancelled at the very beginning, and interrupts execution if condition is true.

```
- (void)main
{
    if (self.isCancelled) return;

    // code
}
```

# UIView

## View is usually initialised in two ways

Either by calling `initWithFrame:`, or `initWithCoder:` method when it is unarchived from a nib file. Both situations are covered.

```
@interface ExampleView ()

@property (strong, nonatomic) UITextField * textField;

@end

@implementation ExampleView

- (id)initWithFrame:(CGRect)frame
{
    self = [super initWithFrame:frame];
    if (self) {
        [self initializeExampleView];
    }
    return self;
}

- (id)initWithCoder:(NSCoder *)aDecoder
{
    self = [super initWithCoder:aDecoder];
    if (self) {
        [self initializeExampleView];
    }
    return self;
}

- (void)initializeExampleView
{
    _textField = [[UITextField alloc] init];
    _textField.translatesAutoresizingMaskIntoConstraints = NO;
    [self addSubview:_textField];

    NSDictionary * views = NSDictionaryOfVariableBindings(_textField);
    [self addConstraints:[NSLayoutConstraint constraintsWithVisualFormat:@"H:|-8-[_textField]-8-|"
                                                                    options:0
                                                                    metrics:nil
                                                                    views:views]];
    [self addConstraints:[NSLayoutConstraint constraintsWithVisualFormat:@"V:|-8-[_textField]-8-|"
                                                                    options:0
                                                                    metrics:nil
                                                                    views:views]];
}
```

Note that we do not implement `encodeWithCoder:` method. UIViews and UIViewControllers does not follow normal serialisation process, their state is persisted in a model.

## The interface of generic view

The view exposes a minimal set of properties and methods that are required for its configuration. If possible, a property is not backed up by an instance variable, but rather by view's or subview's property.

```
- (NSString *)name
{
    return self.nameLabel.text;
}

- (void)setName:(NSString *)name
{
    self.nameLabel.text = name;
}
```

The view is independent of a model. A mapping between view's and model's properties is kept in a category on that view. This way a view controller is kept cleaner.

```
@implementation UITableViewCell (Person)

- (void)configureWithPerson:(Person *)person
{
    self.imageView.image = person.photo;
    self.textLabel.text = person.name;
}
```

## The interface of specific view

The specific view is tightly coupled with model. It exposes one method that takes a model object and configures the view.

```
@interface PersonTableViewCell : UITableViewCell

- (void)configureWithPerson:(Person *)person

@end
```

# UIViewController

## Properties affecting user interface

It is a common practice to have properties on view controller that influence its view. Putting view adjusting code in the setter is not enough, as view may be not loaded. After it is loaded, view controller should adjust it according to the property. In result it is convenient to create a separate method for adjusting the view as it will be called from the setter and `viewDidLoad` as well.

```
- (void)setClient:(Client *)client
{
    _client = client;
    [self adjustUserInterfaceForClient:client];
}

- (void)viewDidLoad
{
    [super viewDidLoad];
    [self adjustUserInterfaceForClient:self.client];
}

- (void)adjustUserInterfaceForClient:(Client *)client
{
    if (self.isViewLoaded == NO) return;
    // code adjusting interface
}
```

## View controller containment

### Container specific items are provided by a property

If a container requires its child to have specific properties, it delivers a category on `UIViewController`. The category provides an item which encapsulates all of the needed properties.

```
- (UINavigationController *)navigationItem
{
    UINavigationController * navigationItem = objc_getAssociatedObject(self, kNavigationItemKey);
    if (navigationItem == nil) {
        navigationItem = [[UINavigationController alloc] init];
        self.navigationItem = navigationItem;
    }
    return navigationItem;
}
```

Whenever container needs to stay in sync with child's properties, it uses Key Value Observing.

## Container is accessible from contained view controllers

Child view controllers can access the container through a property.

```
@interface UIViewController (UINavigationControllerItem)

@property(nonatomic, readonly, retain) UINavigationController *navigationController;

@end
```

The following getter implementation traverses view controller hierarchy, and returns the closest parent view controller of the container class.

```
- (UINavigationController *)navigationController
{
    UIViewController * controller = self.parentViewController;
    while (controller != nil && [controller class] != [UINavigationController class]) {
        controller = controller.parentViewController;
    }
    return (UINavigationController *)controller;
}
```

## The deallocation problem

The dealloc method of UIViewController does things that are not safe to do on a secondary thread, thus it must be deallocated on the main thread.

```
[anObject asynchronousOperationWithCompletionHandler:^(NSData *result) {
    [self processData:result];
}];
```

The foregoing code would cause a problem if implemented in UIViewController subclass as the self is retained by the block. To fix the problem it must be referenced by a weak pointer.

**Tip:** More about the deallocation problem can be found in [Technical Note TN2109](#)

# Core Data

**Important:** `NSObject`'s properties must not be prefixed with "new". Due to `@dynamic` compiler directive, the following compiler error is suppressed: "property's synthesised getter follows Cocoa naming convention for returning 'owned' objects".

## Category provides helper methods to managed object

`NSObject` subclasses can be generated by Xcode schema editor automatically.

```
@interface Person : NSObject

@property (nonatomic, retain) NSString * name;
@property (nonatomic, retain) NSString * surname;

@end
```

Therefore, all helper methods are kept in a category in a separate file, otherwise they would be overridden by the editor.

```
@interface Person (Additions)

- (NSString *)fullName;

@end
```

## Custom objects are stored as transformable attributes

A custom object can be stored by Core Data as a transformable attribute, if it conforms to `NSCoding` protocol. Xcode schema editor uses `id` for this attributes, which deprives developer of good type checking.

```
@interface Person : NSObject

@property (nonatomic, retain) id eyeColorTransformableType;

@end
```

To ameliorate the situation, a property with the proper class type is provided by a category.

```

@interface Person (Additions)

@property (strong, nonatomic) UIColor * eyeColor;

@end

```

Consequently the original property is never used except by the shadowing property's accessors.

```

@implementation Person (Additions)

- (void)setEyeColor:(UIColor *)eyeColor
{
    self.eyeColorTransformableType = eyeColor;
}

- (UIColor *)eyeColor
{
    return self.eyeColorTransformableType;
}

@end

```

## Objective-C types are stored through NSValue

NSValue is a simple container for Objective-C data types. It conforms to NSCodering protocol, thus can be stored by Core Data as transformable attribute.

```

@interface Figure : NSObject

@property (nonatomic, retain) id imaginaryPositionTransformableType; // stores NSValue object

@end

```

A category provides a shadowing property for the convenience.

```

struct ComplexNumber {
    float real;
    float imaginary;
};
typedef struct ComplexNumber ComplexNumber;

extern ComplexNumber const ComplexNumberZero;

@interface Figure (Additions)

@property (assign, nonatomic) ComplexNumber imaginaryPosition;

@end

```

The getter initialises the local variable so it does not return uninitialised value, if the shadowed property is nil.

```
@implementation Figure (Additions)

- (ComplexNumber)imaginaryPosition
{
    ComplexNumber imaginaryPosition = ComplexNumberZero;
    [self.imaginaryPositionTransformableType getValue:&imaginaryPosition];
    return imaginaryPosition;
}
```

The setter creates `NSValue` object with the passed value, and stores it.

```
- (void)setImaginaryPosition:(ComplexNumber)imaginaryPosition
{
    NSValue * value = [NSValue valueWithBytes:&imaginaryPosition objCType:@encode(ComplexNumber)];
    self.imaginaryPositionTransformableType = value;
}

@end
```